

P20-CB/P20-CE TECHNICAL DATA SHEET (hydraulic piston pump for airless painting)

Weight: 87 Kg



MODEL	P20-CB	P20-CE
MAX VOL. FLOW	6,17 l/min	6,17 l/min
MAX PRESSURE	250 bar	250 bar
ENGINE/MOTOR	6 HP - gasoline	3 HP - electric
MOTOR OUTPUT		230 V – SINGLE PHASE
COUPLING	belt	belt
ENGINE-PUMP		

SPRAYABLE PRODUCTS:

acrylic paints, synthetic resin lacquers, 2K materials, emulsions, latex paints, release agents, priming varnishes and primers, fillers, road marking paints waterborne or solvent-based.

Attention: always verify that **materials** used are specifically for **airless application**

AREAS OF APPLICATION:

BUILDING & CONSTRUCTION:
painting, proofing

WOOD & METAL TREATMENT:
structural steelworks,
carpentries

DOCKYARD: shipbuilding, big tanks

ROAD MARKING



Photos don't show standard machine.

ACCESSORIES:

- High pressure filter with manometer
- Suction system: suction hose with mini filter
- Kit for direct suction
- Cock and return hose
- High pressure hose $\frac{1}{4}$ I = 10 m
- Manual gun with 60 mesh filter (without nozzle and nozzle holder)
- Extension for manual gun
- Holder 11/16" for reversible nozzle
- Reversible nozzle

