

Highwayliner - Film laying device



Item number: KAV-HWL

Created on 08.10.2024



Description

Machine for applying temporary marking film

Technical data:

- Motorization: Kawasaki 2 cylinder (Kawasaki FS481V)
- Power: 9.9 kW (13.2 hp)
- Displacement: 603 cm³
- Speed: 12 km/h
- Width: 124 cm, height: 175 cm, length: 210 cm

Basic equipment:

- LED light bar / Nightvision for working at night; including warning lights
- Two-tone paint finish in traffic orange and frame and rims in asphalt grey
- Acoustic 120 dB warning signal system for hazardous situations in noisy road environments
- Foldable and space-saving platform for carrying on-board tools and maintenance utensils
- Anti-flat tire inflation to make flat tires on the construction site a thing of the past
- Collision protection plus: collision and front protection bar, protection for body and frame with
- 12,000 lumen LED flood work lights
- Joystick & control panel Pro: Intuitive one-finger operation of all functions during the laying process.

Description

Monitoring of the process parameters

- Magazine and transport trolley for transporting up to 550 meters of marking film
- 6 x holder for pre-marking rods (3 x left, 3 x right, internal dimensions max. 20 mm x 20 mm)

Integrated VERLEGEEINHEIT road marking film

- The marking film is guided onto the road surface via deflection rollers. The marking film is fed depending on the driving speed.

- Functions selected via the joystick & control panel Pro are reliably executed by the laying unit via pneumatically driven movements

- Designed for marking films with 12 cm and 15 cm wide display visor made of robust steel
- Visor can be individually adapted to the conditions
- Decoupled central connection via a clamp connection with the steering of the Highwayliner

Integrated PRIMATIK automatic primer spray system

Automatic primer spraying system for priming work with 3M & Snoline primers.

Functions:

- Space-saving, plug-in stainless steel mounting bracket for primer canisters
- Employee-friendly attachment at the end of the vehicle (harmful vapors only arise behind the driver)
- Modular spray head, primer work for 12 cm and 15 cm wide marking film
- Corrosion-resistant processing for frequent cleaning with solvents

Spare parts

Accessories/Extensions