



NOISE-STOP® is a special rubber system designed to adapt to all the different shapes of covers for manholes, drains and grids on the streets. **NOISE-STOP®** simply works once inserted into the space between the frame and the cover of each manholes, drains or grids, it acts as a shock absorber between the two parts whenever a vehicle passes over it.



NOISE-STOP® and the material it is made of is designed to withstand the various weather conditions that occur season after season. Indeed **NOISE-STOP®** is long lasting, easy to apply and reduce cost of maintenance for the street increasing its safety. It is in fact the one and only solution to noise pollution in Urban and rural areas worldwide.



| SERIES | LIGHT NOISE (15) | MEDIUM NOISE (20) | HEAVY NOISE (30) |
|------------------------|--------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| CODE | 15-LFN | 20-LFN | 30-LFN |
| THICKNESS | 1,5 mm | 2,0 mm | 3,0 mm |
| DIMENSIONS | 20 X 60 X 150 mm | 60 X 120 X 180 mm | 20 X 60 X 160 mm |
| COLOR | BLACK | BLACK | BLACK |
| MATERIAL | LONG-LIFE® | LONG-LIFE® | LONG-LIFE® |
| HARDNESS | 80 Sh | 80 Sh | 80 Sh |
| CATEGORY (DESTINATION) | C250 | D400 | C250 + D400 |
| APPLICATION | LIGHT TRAFFIC STREETS LIGHT TILTING EFFECT LIGHT COVERS FULLFILL SMALL GAPS | MEDIUM/HIGH TRAFFIC STREETS MEDIUM TILTING EFFECT HEAVY AND WIDE COVERS FULLFILL SMALL/MEDIUM GAPS | HIGH TRAFFIC STREETS HIGH TILTING EFFECT HEAVY COVERS FULLFILL HUGE GAPS |

DESIGN FULLY PATENTED AS NOISE SHOCK ABSORBER

MAIN FEATURES

| | | | | | |
|----------------------------------|------------------------|-----------------------------------|---------------------------------------|--------------------------|-----------------------------------------|
| - 40 / + 110 °C TEMP SERVICES | ALL-SEASON EFFICACY | PATENTED MATERIAL LONG LIFE | 1 TO 2 YEARS AVERAGE LIFE CYCLE | EFFECTIVE IMMEDIATELY | ADAPTABLE TO ALL SHAPES OF COVERS |
|----------------------------------|------------------------|-----------------------------------|---------------------------------------|--------------------------|-----------------------------------------|



Values and coefficients contained in this sheet are for information only and shall in no event be held to constitute or imply any warranty, undertaking, express or implied commitment. No liability whatsoever can be accepted by ITG SPA with respect to difference to the values reported in the tables or misuse by the Customer of the product.